



AC 750-10-0000

• AC Line Input: 115 or 208/230 VAC

Phase: single-phaseDrive Output: 0-230 V

• Continuous Current: 2.4 amps

• Peak Current: 9.6 amps • Max Power: 0.5 hp

Size: 3.9 x 4.3 x 2.75 inches
Direction: forward/reverse
Enclosure Type: chassis



AC 750-10-0001

• AC Line Input: 115 or 208/230 VAC

Phase: single-phaseDrive Output: 0-230 V

• Continuous Current: 4.0 amps

• Peak Current: 14.0 amps

• Max Power: 1 hp

Size: 4.3 x 4.7 x 5 inches
Direction: forward/reverse
Enclosure Type: chassis



AC 750-10-0002

• AC Line Input: 115 or 208/230 VAC

• Phase: single-phase

Drive Output: 0-208/230 V
Continuous Current: 3.6 amps

• Peak Current: 14.4 amps

• Max Power: 1 hp

Size: 9.5 x 5.5 x 5.9 inches
Direction: forward/reverse

• Enclosure Type: NEMA 4X



AC 750-10-0003

• AC Line Input: 115 or 208/230 VAC

Phase: single-phaseDrive Output: 0-230 V

• Continuous Current: 1.0 amp

• Peak Current: 4.0 amps
• Max Power: 0.1 hp
• Size: 3.9 x 4.3 x 2.3 inches
• Direction: forward/reverse

• Enclosure Type: chassis



AC 750-10-0004

• AC Line Input: 115 or 208/230 VAC

Phase: single-phaseDrive Output: 0-230 V

• Continuous Current: 1.0 amp

• Peak Current: 4.0 amps

Max Power: 0.1 hp
 Size: 6.1 x 3.9 x 3.7 inches

Size: 6.1 x 3.9 x 3.7 inches
Direction: forward/reverse
Enclosure Type: NEMA 1



AC 750-10-0005

• AC Line Input: 115 or 208/230 VAC

Phase: single-phaseDrive Output: 0-230 V

• Continuous Current: 2.2 amps

• Peak Current: 4.0 amps

• Max Power: 0.5 hp

Size: 6.1 x 3.9 x 3.7 inches
Direction: forward/reverse
Enclosure Type: NEMA 1



BLDC 750-30-0002

• Voltage: 12-48 VDC

• Continuous Current: 7.5 amps

Peak Current: 11.3 amps
Speed Range: 60:1
Size: 4.25 x 3.62 x 1.3 inches
Direction: forward/reverse
Enclosure Type: chassis



BLDC 750-30-0003

• Voltage: 12-48 VDC

• Continuous Current: 7.5 amps

Peak Current: 11.3 ampsSpeed Range: 60:1

• Size: 7.15 x 5.53 x 4.32 inches

• DC Signal: 0-5 V

Direction: forward/reverse
Enclosure Type: NEMA 4X



BLDC 750-30-0004

• Voltage: 12-48 VDC

Continuous Current: 20 ampsPeak Current: 40 amps

• Speed Range: 60:1

Size: 7 x 3.62 x 2.11 inches
Direction: forward/reverse
Enclosure Type: chassis

Sold & Serviced By:



Toll Free Phone (877) SERV098 www.electromate.com sales@electromate.com



BLDC 750-30-0005

• **Voltage:** 12-48 VDC

• Continuous Current: 20 amps

Peak Current: 40 ampsSpeed Range: 60:1

Size: 9.53 x 5 x 4.63 inches
Direction: forward/reverse
Enclosure Type: NEMA 4X



BLDC 750-30-0006

• Voltage: 12-48 VDC

• Continuous Current: 8 amps

• Peak Current: 12 amps

• Size: 4.93 x 3.62 x 2.29 inches

• Direction: forward/reverse

• Enclosure Type: NEMA 4X



DC 750-22-0003

Input Voltage: 115/230 VAC
Output Voltage: 90-180 VDC

• Continuous Current: 3 amps

• Peak Current: 6 amps

• **Size:** 5.53 x 3.62 x 2.70 inches

• Direction: forward

• Enclosure Type: NEMA 4/12