Accessories


Collapsable Bellows


Bellows will reduce available stroke length of slide by approximately 28%. Bellows P/N should be succeeded by a length when ordering.

Bellows Materials:

- Polyester Cover
- PVC Stiffeners

BEL-1B[†] (For 1BA) Moveable Protective Bellows (Dimensions in inches)







➡B —►	Part Number	Nominal Shaft Diameter	н	H1	В	CR
	BEL-1B-04	1/4	1.187	.906	1.182	.163
	BEL-1B-06	3/8	1.312	.968	1.937	.108
	BEL-1B-08	1/2	1.687	1.156	2.062	.160
	BEL-1B-12	3/4	2.000	1.156	2.312	.108
	BEL-1B-16	1	2.375	1.281	2.625	.163
➡-B1-➡	BEL-1B-24	1 1/2	3.062	1.531	3.125	.108

† Each moveable bellows comes with 1 section of bellows and 2 pairs of Velcro® Fasteners.

BEL-1C[†] (For 1CA) Moveable Protective Bellows (Dimensions in inches)






Part Number	Nominal Shaft Diameter	Н	H1	В	CR
BEL-1C-08	1/2	1.375	.968	2.062	.088
BEL-1C-12	3/4	1.812	1.062	2.312	.120
BEL-1C-16	1	2.375	1.218	2.625	.088
BEL-1C-24	1 1/2	3.125	1.531	3.125	.088

† Each moveable bellows comes with 1 section of bellows and 2 pairs of Velcro® Fasteners.

BEL-2D (For QuickSlide System 2DA) Dual Shaft Rail Bellows (Dimensions in inches)






Part Number **Nominal Shaft Diameter** H1 В н BEL-2DA-08 1.50 .85 4.60 1/2 BEL-2DB-08 1/2 1.89 1.34 5.13 BEL-2D-12 3/4 2 406 1.437 6.00 BEL-2D-16 2 875 1.687 7.50

Each moveable bellows comes with 1 section of bellows and 2 mounting brackets and mounting screws. † Appropriate arrangements for afixing the Bellows at each end of the QuickSlide 2DA System are required.

BEL-2C-H (For Horizontal Twin Shaft Web QuickSlide System 2CA) Moveable Protective

Bellows (Dimensions in inches)






Part Number	Nominal Shaft Diameter	H	H1	В	CR
BEL-2C-08-H	1/2	1.688	1.031	3.250	.108
BEL-2C-12-H	3/4	2.062	1.156	3.812	.108
BEL-2C-16-H	1	2.437	1.281	4.62	.108
Each may apple ballows some with 1 section of ballows and 2 pairs of Valers® Easteners					

Each moveable bellows comes with 1 section of bellows and 2 pairs of Velcro[®] Fasteners.

BEL-2C-V (For Vertical Twin Shaft Web QuickSlide System 2CA) Dual Shaft Rail Bellows (Dim. in in.)



Part Number	Nominal Shaft Diameter	Н	H1	В	CR
BEL-2C-08-V	1/2	2.750	1.000	2.125	.163
BEL-2C-12-V	3/4	3.750	1.125	2.375	.163
BEL-2C-16-V	1	4.375	1.250	2.625	.108

Each moveable bellows comes with 1 section of bellows and 2 pairs of Velcro® Fasteners.



Sold & Serviced By:

FLFCTRON

www.electromate.com sales@electromate.com