

Sold & Serviced By:



Toll Free Phone (877) SERV098
Toll Free Fax (877) SERV099
www.electromate.com
sales@electromate.com

H4 Handheld

Secure Mobility HMI in your Hand



Key Features

Certified Wireless Safety SIL2

JMobile Integrated

Easy to Program

Stunning Design/Ergonomics

Multiple Integrated Keys

Potentiometers

Handwheel

State Selector

Bluetooth Safety

Additional WiFi Connectivity

Magnets to Hang Devices in
Convenient place

Up to 50 m Connection

H4 Handheld

The H4 Handheld device is a true HMI in your hand: powerful and easy to program to your needs it remains the perfect choice for safe mobile requirements.

The wireless option leads to many positive features being enhanced:

- Higher Safety in all areas with no pendant wires to causes issues
- Less injury risks
- No broken cable downtime
- Far less physical fatigue of operator
- Increased concentration of operator

The wireless connection is provided by a Unique electronic key which allows for multiple handheld – machine connections to take place simultaneously without any concern for connectivity and of course safety.



H4 Handheld - Technical Data

| System Resources | |
|---------------------------------|---|
| Display - Colors | TFT LED - 64K |
| Resolution | 480x272, WQVGA |
| Brightness | 300 Cd/m ² typ. |
| Dimming | to 0% |
| Touchscreen | Resistive |
| CPU | ARM Cortex-A8 - 600 MHz |
| Operating System | Microsoft Windows CE 6.0 |
| Flash | 128 MB |
| RAM | 256 MB |
| Real Time Clock, RTC Back-up | Yes |
| Handwheel | Yes |
| Potentiometer | 2 |
| State Selector Switch | 16 positions |
| Emergency stop | Yes |
| Enabling Switch | 3 positions |
| Interface | |
| Ethernet | Wi-Fi 802.11 |
| USB port | 1 Host V2.0 |
| Bluetooth | Reserved for safety functions |
| Ratings | |
| Power supply (charging station) | 24 Vdc (18 to 30 Vdc) |
| Current Consumption | 0.25 A at 24 Vdc (max.) |
| Input Protection | Automatic |
| Battery | Rechargeable Lithium battery, not user-replaceable |
| Environment Conditions | |
| Operating Temp | +5 to +45°C |
| Storage Temp | -20 to +70°C |
| Operating / Storage Humidity | 5-85% RH, non condensing |
| Protection Class | IP64 |
| Dimensions and Weights | |
| Faceplate LxH | 220x144 mm |
| Depth D | 63 mm |
| Weight | Approx 0.8 Kg |
| Approvals | |
| CE | Emission EN 61000-6-4 Immunity EN 61000-6-2 for installation in industrial environments |
| Safety | 2006/42/EC, EN ISO 13849-1:2008, EN 62061 :2005/A1:2013, EN 60204-1:2006/A1:2009 |
| Safety functions | Emergency Stop cat 3, PL d / SIL 2 Enabling cat 3, PL d / SIL 2 State selector, cat 1, PL c / SIL 1 |

Sold & Serviced By:

 **ELECTROMATE**

Toll Free Phone (877) SERV098

Toll Free Fax (877) SERV099

www.electromate.com

sales@electromate.com



EXOR