

Plug connection (20 ... 80 mm)	Plug connection (30 ... 200 mm)
<p style="text-align: right;">153-00839</p>	<p style="text-align: right;">153-00837</p>

Connection, 4-pin, IO-Link	Light spot size
<p style="text-align: right;">154-00575</p>	<p style="text-align: right;">155-01663</p>

Scanning properties FT 25-RA-60	Scanning properties FT 25-RA-170
<p style="text-align: right;">155-01666</p>	<p style="text-align: right;">155-01667</p>

Characteristic output and analogue curves	Default settings										
<p style="text-align: right;">155-01661</p>	<table border="1"> <tr> <td></td> <th data-bbox="1165 1724 1353 1792">FT 25-RA-60</th> <th data-bbox="1353 1724 1548 1792">FT 25-RA-170</th> </tr> <tr> <td>Analogue output Q_A (1 ... 10V)</td> <td>20 ... 80 mm</td> <td>30 ... 200 mm</td> </tr> <tr> <td>Switching output Q (A1 ... A2), N.O.</td> <td>20 ... 80 mm</td> <td>30 ... 200 mm</td> </tr> </table>		FT 25-RA-60	FT 25-RA-170	Analogue output Q_A (1 ... 10V)	20 ... 80 mm	30 ... 200 mm	Switching output Q (A1 ... A2), N.O.	20 ... 80 mm	30 ... 200 mm	
	FT 25-RA-60	FT 25-RA-170									
Analogue output Q_A (1 ... 10V)	20 ... 80 mm	30 ... 200 mm									
Switching output Q (A1 ... A2), N.O.	20 ... 80 mm	30 ... 200 mm									
	Accessories										
	<ul style="list-style-type: none"> Connection cables Brackets Sensolo (901-01001) 	www.sensopart.com/en/accessories									